

2A30M

ex 1/S C

SERRATURA DA APPLICARE SCREW-ON LOCK

SERIE
2A

2A30M

1/S C

FUNZIONAMENTO

Rotazione 360° (2 uscite chiave)

Rotazione 320° (1 uscita chiave)

SCATOLA IN ZAMA

Nichelato

Ottonato

Nero

Bronzato

CILINDRO Ø 17

mm 20

mm 22

mm 25

mm 30

Cilindro numerato

CIFRATURE

KD chiavi differenti

KA chiavi uguali

Gruppi di KA

Chiave maestra

CHIAVI

Art.82 nichelata (2 pz)

Art.82PU nero (2 pz)

Art.82PU grigio (2 pz)

FINITURE

US14 nichelato

Ottonato

Bronzato

Nero

CATENACCI

Piano

Piegato mm 3,5

Piegato mm 7,5

Piegato mm 10

Piegato mm 12

Piegato mm 15

ACCESSORI

1 ghiera Art.401

1 controbordo Art.608

CONFEZIONI

Commercio 20 pz

Industria 100 pz

1/S C

OPERATION

Rotating 360° (2 key pull)

Rotating 320° (1 key pull)

DIE CAST BODY

Nichel plated

Brass plated

Black

Bronze plated

CILYNDER Ø 43/64"

25/32"

55/64"

63/64"

1 3/16"

Numbered cylinder

KEY-CHANGES

KD keyed differently

KA keyed alike

KA in groups

Master key

KEYS

Art.82 nickel plated (2 pcs)

Art.82PU black (2 pcs)

Art.82PU grey (2 pcs)

FINISHES

US14 nickel plated

Brass plated

Bronze plated

Black

BOLTS

Flat

Bent 9/64"

Bent 19/64"

Bent 25/64"

Bent 15/32"

Bent 19/32"

ACCESSORIES

1 ring Art.401

1 striking plate Art.608

PACKAGING

Boxed in 20's

Bulk in 100's

